
















SMART LED LIGHTS

Niche / Stand / Nozzle Mounted Light

AQVASTAR - All Stainless Steel Pool / Fountain, Niche / Stand / Nozzle mounted lights are unique in design with unparalleled finish & quality



Technical specification

Ref. Code	Led Brand	Power Options	Control Options	Voltage	Beam Angle	Light Description
ASNSM3SS ASNSM6SS	CREE	3W 6W	Single Color	12V/24V AC/DC	15°	Long irradiation distance Concentration effect
			RGB	12V/24V AC	30°	
			RGB(4 Wires)	12V/24V DC	45°	
		6W(RGBW)	RGBW(5 Wires)	12V/24V DC	60° 90°	
ASNSM9SS ASNSM12SS ASNSM18SS	CREE	6W 9W 12W 18W	Single Color	12V/24V AC/DC	15° 30° 45° 60° 90°	Long irradiation distance Concentration effect
			RGB	12V/24V AC		
			RGB(4 Wires)	12V/24V DC		
			DMX512	12V/24V DC		
		12W(RGBW)	RGB	12V/24V AC		
			RGBW(5 Wires)	12V/24V DC		

Ref. Code	Led Brand	Power Options	Control Options	Voltage	Beam Angle
ASRL9SS1	CREE	6W 9W 15W	Single Color	12V/24V AC/DC	15° 30° 45° 60° 90°
ASRL15SS1			RGB	12V/24V AC	
			RGB(4 Wires)	12V/24V DC	
		DMX 512	12V/24V DC		
ASRL9SS2 ASRL12SS2 ASRL18SS2		CREE	15W(RGBW)	RGB	
	RGBW(5 Wires)			12V/24V DC	
	9W 12W 18W		Single Color	12V/24V AC/DC	
			RGB	12V/24V AC	
			RGB(4 Wires)	12V/24V DC	
			DMX 512	12V/24V DC	
			18W(RGBW)	RGB	12V/24V AC
RGBW(5 Wires)	12V/24V DC				

Note: Standard Angle is 120° for Stand & Niche mounted lights
Standard Angle is 45° for Ring lights.

Product Details

Body Material
Stainless steel 316/304

Lifespan
≥50,000 Hours

Wire
VDE Certification

Lens Material
8mm thickness
tempered glass

Working Temperature
-20°C ~ 40°C

Light Source
CREE