
COMPETITION EQUIPMENTS

- 1 Ladder
- Starting block
- Overflow grate
- 4 Lane ropes
- Backstroke flags
- 6 Turning panel with supports

Competition Pool Layout





Starting Block

Starting block that usually consists of two blocks mounted on either side with a frame and that provides a runner with a rigid surface against which to brace the feet at the start of a race.

- Electropolished 316 stainless steel stand.
- Height 355 mm/ 700mm (Other sizes on request).
- 700mm height starting block comes with additional back step.
- Supplied with fixed backstroke starting handle.
- Supplied with 50x50 cm. FRP, anti-slip platform.
- Supplied with stainless steel screw fittings and adhesive numbers (Optional).
- · Complies with FINA facility rules.





Adjustable starting Block

These starting blocks are of adjustable type so that swimmers could able to adjust the position in relation to the opening line.

There is a lever in side of starting block by which adjustment is possible. Position also marked in side of starting block so the swimmers could adjust before getting in block.

- Electropolished 316 stainless steel stand.
- Height 385 mm / 750 mm (Other sizes on request)
- 750mm height starting block comes with additional back step.
- Supplied with fixed backstroke starting handle.
- Supplied with 50x50 cm. FRP, anti-slip platform.
- Supplied with stainless steel screw fittings and adhesive numbers (Optional).
- Top platform can be adjustable to 60 mm (Front & back)





COMPETITION EQUIPMENTS

Float Lane

Float Lane Rope: Segregates competition lanes and to eliminates any turbulence (by the rotation of individual floats) which may pass from one lane to another when swimmers are racing.

- High-Quality PP disks with additives resistant to chemicals and weather agents.
- Disk diameter 100 mm. (10 per metre).
- Disks designed to reduce turbulence.
- Assembled on SS316 wire rope, dia 6 mm (Plastic Rope as optional).
- 4 colours: blue, red, yellow and green according to FINA rules.
- Supplied with stainless steel spring and tensioner.



Cup Anchor

Anchor cup in stainless steel with hinged hook retaining arm lane rope has been connected with this cup.
Flat above deck option also available (as per picture).

- Electropolished 316 stainless steel.
- Square flange 80x80 mm.
- Plate for securing the lane.
- · Supplied with brackets for improved installation



Back Stroke Turn Indicators

Situated 5m from each end of the pool, are a line of flags crossing the water to warn backstroke swimmers that they are nearing the end of the pool so that they can prepare for their turn. Made with a pole of 48.3mm dia.

- 2 x SS316 Back Stroke poles of FINA regulation height 2 m.
- 1 x Back Stroke flags & ropes.
- 2 x Deck pole anchors.
- Three sizes available to suit 13m, 21m,& 25m wide pool.
 Custom sizes also available with adequate notice.
- Custom flag printing available to suit your pool or club with adequate notice.






COMPETITION EQUIPMENTS

False Start Indicators

Situated 5 metres from one end of the pool, are a line of floats crossing the water to inform swimmers that the race is abandoned. Made with a pole of 48.3 mm dia and supplied with hooks on the ends for attaching ropes or snap-hooks.

- 2 x SS316 false start poles of FINA regulation height 2 Mtr.
- 1 x false start rope & fittings.
- 2 x deck pole anchors.
- Three sizes available to suit 13m, 21m & 25m wide pool. Custom sizes also available with adequate notice.



Float Lane Roller

- XL Capacity float lane roller made from SS316 pipes comes with heavy duty, non-marking and locking casters can swivel 360° and easy to maneuver.
- Capable to hold 6 float lane of 25mtr long or 3 float lane rope of 50mtr long.



Life Guard Chair

- Frame made of SS316, with a 43mm / 38mm dia tubing.
- The threads, seats are made of plastic.
- Base from SS316 with wheels.



