

POOL BASIN FITTINGS - ABS

Main Drain - For residential pools

- Manufactured in ABS.
- Main drains available with flat drain grille.
- Recommendation - Main drains must be arranged Properly so that there is no risk of bathers being drawn towards them or trapped there.
- It is recommended that on all installations, a minimum of 2 main drains are installed 2 meters apart.
- Threaded type.



Ref. Code	Product Description
ASCMD200	8" Main drain with anti entrapment grille – 18 m ³ /h – Concrete pools

Main Drain - For commercial pools

- Manufactured in ABS.
- Main drains available with flat drain grille.
- Recommendation - Main drains must be arranged Properly so that there is no risk of bathers being drawn towards them or trapped there.
- It is recommended that on all installations, a minimum of 2 main drains are installed 2 meters apart.



Ref. Code	Product Description
ASMD225	Square Main Drain 225x225mm - Frame & Grille in ABS 20 m ³ /h
ASMD300	Square Main Drain 300x300mm - Frame & Grille in ABS 33 m ³ /h
ASMD450SF	Square Main Drain 450x450mm - Frame in SS & Grille in ABS 80 m ³ /h
ASMD600SF	Square Main Drain 600x600mm - Frame in SS & Grille in ABS 132 m ³ /h

Wall Inlets

- Manufactured in ABS.
- Wall inlet allows easy control of flow into the pool by adjusting the angle of the ball.
- Recommended Flow 5 m³/h - 9 m³/h.
- Solvent /threaded type.
- Dimension: Ø 105 x 58 H mm



Ref. Code	Product Description
ASWIT	Adjustable Wall inlet 2" threaded
ASWIS	Adjustable Wall inlet 63mm - Solvent

Floor Inlets

- Manufactured in ABS.
- Adjustable floor inlet allows easy control of flow into the pool by adjusting the screw available.
- Recommended flow 9 m³ /h - 12 m³ /h.
- Solvent /threaded type.
- Dimension: Ø 107 x 65 H mm



Ref. Code	Product Description
ASFIT	Adjustable floor inlet Standard 2" Threaded
ASFIS	Adjustable floor inlet Standard 63mm Solvent
ASFIDT	Adjustable floor inlet Diffuser 2" Threaded
ASFIDS	Adjustable floor inlet Diffuser 63mm Solvent

POOL BASIN FITTINGS - ABS

Vacuum Point

- Manufactured in ABS.
- Vacuum point is installed where an automatic pool cleaner or vacuum hose is to be fitted.
- These fittings are supplied with removable plug.
- Solvent / Threaded type.
- Dimension: Ø 105 x 58 H mm

NOTE: Solvent fittings suitable for 10kg/6kg grey colour pipe.



Ref. Code	Product Description
ASVPT	Vacuum point & Plug 2" Threaded
ASVPS	Vacuum point & Plug 63mm Solvent

Overflow Fitting

- Manufactured in ABS
- Suitable for overflow channels required to drain out water to balancing tank.
- Recommended flow 7 m³/h.
- Solvent type.
- Dimension: 110 x 97 H mm



Ref. Code	Product Description
ASOFF	Gutter drain 50mm

Wall Conduit


- Manufactured in ABS/PP.
- 300mm Long conduit, can be easily cut to required lengths
- Depending on pool shell thickness, have puddles for positioning within the pool shell.
- Solvent end - Back side to suit pipe of 50mm.
- Threaded end - Front side to suit pools fittings 2"



Ref. Code	Product Description
ASWC	Wall conduit for 2" threaded fitting

Overflow Grating

- Manufactured in ABS/PP with UV Protection.
- Comes in 250/300mm Wide.
- Single spine connection.
- Anti slip surface.



Ref. Code	Product Description
ASOFF250	Overflow gratings 250mm Wide
ASOFF300	Overflow gratings 300mm Wide

Main Drain Grille

- Manufactured in ABS
- Available for Concrete & pre fabricated pools
- Grille cover diameter is 150mm



NOTE: White & Half white available | All colours made available against orders | Granite & Marble finish fittings available against orders

Ref. Code	Product Description
ASCMD150G	Circular Main Drain- Antivortex Frame & Grille in ABS 18 cu mtr/hr
ASCMD150F	Circular Main Drain- Flat Frame & Grille in ABS 18 cu mtr/hr

POOL BASIN FITTINGS - ABS

Corner Grating

- This Corner Grating is used to ensure pool corners finished safely matching over flow gratings.
- 90° overflow corner gratings made in PP, matching grating colour of half white.
- This comes with non slip finish.



Ref. Code	Product Description
ASCG250	Corner gratings 250mm PPG
ASCG300	Corner gratings 300mm PPG

Overflow grating Profile

- This Profile is used to ensure the grating is inline with deck area.
- Suitable for 22, 24, and 35 mm high gratings.
- Made in PP.
- Supplied in 1.5 mtr lengths.



Ref. Code	Product Description
ASGP	Grating Profile - 1.5 metre Long