

POOL BASIN FITTINGS - SS

Main Drain - for Residential pools

- Manufactured in SS.
- Main drains available with Flat grille and a frame.
- Recommendation - Main drains must be arranged properly so that there is no risk of bathers being drawn towards them or trapped there.
- It is recommended that on all installations, a minimum of 2 main drains are installed 2 meters apart.



Ref. Code	Product Description
ASCMD150SS	Circular Main Drain- Frame in ABS & Grille in SS-18 m3/h

Main Drain - for Commercial pools

- Manufactured in SS.
- Main drains available with Flat grille and a frame.
- Recommendation - Main drains must be arranged properly so that there is no risk of bathers being drawn towards them or trapped there.
- It is recommended that on all installations, a minimum of 2 main drains are installed 2 meters apart.



Ref. Code	Product Description
ASMD225SS	Square Main Drain 225 x 225mm- Frame in ABS & Grille in SS 20 m3/h
ASMD300SS	Square Main Drain 300 x 300mm - Frame in ABS & Grille in SS 33 m3/h
ASMD500SS	Square Main Drain 500 x 500mm - Frame & Grille in SS 100 m3/h

Wall Inlets

- Manufactured in SS.
- Recommended flow 9 m³/hr.
- Threaded type.
- Dimension: Ø 72 x 53 H mm



Ref. Code	Product Description
ASWISC	SS Adjustable Wall inlet Circle 2" threaded
ASWISS	SS Adjustable Wall inlet Square 2" threaded

Vacuum Point

- Manufactured in SS.
- Vacuum Point is installed where an automatic pool cleaner or vacuum hose is to be fitted. These fittings are supplied with movable plug.
- Dimension: Ø 77 x 58 H mm



Ref. Code	Product Description
ASVPSC	SS Vacuum point & plug circle 2" threaded
ASVPSS	SS Vacuum point & plug square 2" threaded

POOL BASIN FITTINGS - SS

Floor Inlet

- Manufactured in SS.
- Floor inlet allows easy control of flow into the pool by adjusting the centre screw.
- Recommended flow 12 m³/h.
- Threaded type.
- Dimension: Ø 77 x 58 H mm



Ref. Code	Product Description
ASFISC	SS Adjustable floor inlet circle 2" threaded
ASFISS	SS Adjustable floor inlet square 2" threaded

Overflow Fitting

- Manufactured in SS Top cover available with flat grille.
- Recommended flow 7 m³/h.
- Solvent type.



Ref. Code	Product Description
ASOFFSS	SS Gutter drain Top 50 mm - PVC

Overflow Grating

- Overflow gratings are available in SS316 with single spine connection
- Suitable for straight/curved pool channels.
- Available in 200, 250, 300 mm as standard.
- Non standard sizes available on request.



Ref. Code	Product Description
ASOFF250SS	Overflow gratings 250mm in SS - in metre
ASOFF300SS	Overflow gratings 300mm in SS - in metre

Note: Push-fit with O-ring for 63mm PVC pipe available on request for wall inlet, floor inlet and vacuum point