

SPA FITTINGS - ABS



| Ref. Code | Product Description |
|-----------|---|
| ASJN5032 | Spa nozzles with a flow rate of 4.5 cu.mtr. water connection 50mm & air connection 32mm |

| Ref. Code | Product Description |
|-----------|---|
| ASSPD | Antivortex suction in ABS with 1.5" / 2" connections |
| ASCPSPD | Antivortex suction Chrome Plated with 1.5" / 2" connections |

JACUZZI NOZZLE

- Manufactured in ABS.
- These high performance spa jets shall allow clients to have complete control of pressure and direction. Jets turn on/off by rotating the nozzle or jet face. Jets can be easily removed from inside the tub for servicing or cleaning.
- Flow 4.5 cu mtr/h @ 0.8 BAR.
- Connection size of 50 x 32 mm.
- Nozzle suitable for BS & ASTM pipes (Pls refer while ordering)

WALL MOUNTED DRAIN

- Manufactured in ABS & top cover chrome plated.
- Wall mounted installations.
- Hi-Flow rating of 128 GPM.
- Available in ABS/ CP FACIA- 1 1/2" sizes.
- Total open Area: 4.01 sq. in.



| Ref. Code | Product Description |
|-----------|--|
| ASBLN | Air Bubbler nozzle with 20 mm Connection |

| Ref. Code | Product Description |
|-----------|--|
| ASAVC | Air volume controller to regulate the air flow in the nozzle |

AIR BUBBLER NOZZLE

- Manufactured in ABS.
- Bubbler nozzle allows air into pool with air pipe network.
- Comes with tube/ solvent/ threaded connections so that it is easy to connect with pipe network.

AIR CONTROLLER

- Manufactured in ABS.
- Air controller capable of allowing air into the pipe network with the venturi arrangement available in jacuzzi nozzles.
- Comes with solvent/ threaded connections so that it is easy to connect with pipe work.
- Top Portion is adjustable enabling quantity of air movement in to pipe network

SPA FITTINGS - ABS



| Ref. Code | Product Description |
|-----------|---|
| ASPB | Push button ABS with 1" threaded connections. |

| Ref. Code | Product Description |
|-----------|---|
| ASPNS | Pneumatic switch for pump control panel to connect the push button. |

PUSH BUTTON

- Manufactured in ABS.
- These air buttons push air to your controller to operate the blower.
- Air buttons are located at spa-side and are used to control the air switches which are connected to your spa equipment.
- It comes with Threaded connection / Check nut
- 3-4 mm Air tube connection.

PNEUMATIC SWITCH

- Manufactured in ABS.
- Single function control switches provide safe actuation of electrical devices from remote locations.
- Connected with 3-4 air tube on one side & other side connected with pump control panel.



| Ref. Code | Product Description |
|-----------|---------------------|
| ASAT | Air Tube Per Meter. |

AIR TUBE

- Manufactured in PP.
- Coil of Air tube is 15 mtr length.